



BASIC FEATURES

AGE GROUP: 18 months to 5 years old
FALL HEIGHT (CSA): 16" (0,4m) (ASTM): 16" (0,4m)
CHILD CAPACITY: 1 child
DIMENSION (WT x DT x HT): 1'9" x 3'2" x 2'6" (0,5m x 1m x 0,8m)
SHOCK ABSORBING SURFACE (CSA): 14' x 16' (4,3m x 4,9m)
SHOCK ABSORBING SURFACE (ASTM): 14' x 16' (4,3m x 4,9m)



DESCRIPTION

Its attractive "enveloping" sides, easy access from the front, flat seat, step and grab handles that are the perfect diameter for little hands make this model of spring rider ideal for younger children and children with motor challenges.

ANCHORING



ON STRINGERS

This product is anchored to the ground by a system of galvanized steel stringers. Some parts of the stringers may be made of recycled plastic.

MATERIALS

PLASTIC MATERIALS

Plate(s) and panel(s): Panels and other plastic parts are made of HDPE polyethylene colored in the mass and treated against UV rays. All edges are rounded for maximum safety.(lv)
Handel(s) and step(s): Made of HDPE polyethylene colored in the mass and treated against UV rays.

METALS

Spring(s): Helical type anti-pinch 5/8" (16mm) diameter rod. Fixing to its ends by heavy-duty brackets.
Hardware: Made of stainless steel, camouflaged by HDPE safety caps.

COATINGS

Paint: Painted metal parts are white blasted first, then coated with a primer and Z-series polyester powder, which has an extreme resistance to ultraviolet (UV) rays and weather. (lv)
Galvanization: Some attachments are hot dipped galvanized.

COLOUR CHOICES

Polyethylene Panels (3/4")



Made at our factory in Lévis, Québec, Canada • Meets CAN/CSA-Z614 and ASTM ASTM F1487