



## BASIC FEATURES

AGE GROUP: **5 to 12 years old**  
 FALL HEIGHT (CSA): **150" (3,8m)** (ASTM): **150" (3,8m)**  
 CHILD CAPACITY: **21 children**  
 SHOCK ABSORBING SURFACE (CSA): **24' x 25' (7,3m x 7,6m)**  
 SHOCK ABSORBING SURFACE (ASTM): **24' x 25' (7,3m x 7,6m)**

## DESCRIPTION

A beautiful mix of flexible cables and rubber straps. This climber offers a coordination and strength development challenge for different muscle groups.

## BODY MOVEMENTS

 **Climbing**  
 Intensive (10)

 **Pulling up**  
 Intensive (10)

 **Socializing**  
 Moderate (5)

 **Balancing**  
 Intensive (10)

 **Hanging**  
 Intensive (10)

## MATERIALS

### FLEXIBLE MATERIALS

**Cable(s):** Cable 5/8" (16 mm) in diameter composed of 6 strands of 8 galvanised steel wires each, wrapped with black polyester, linked together using aluminium joints.

**Rubber:** 1/4" thick rubber strap made of two rubber layers laminated with two polyester linings. The top has a non-skid texture and the lining is visible on the underside.

### METALS

**Post(s):** 6061-T6 aluminum alloy tube measuring 5" (127mm) in outer diameter, with 0.125" wall thickness.

**Hardware:** Made of stainless steel, Anti-vandal type.

**Hardware:** Made of stainless steel, camouflaged by HDPE safety caps.

### PLASTIC MATERIALS

**Plate(s):** Panels are made of HDPE polyethylene colored in the mass and treated against UV rays. All edges are rounded for maximum safety.(IV)

**Transparent Material:** 1/2" colored translucent resin panel

## ANCHORING



**IN CONCRETE**  
 This product is anchored to the ground with concrete columns.

## COLOUR CHOICES

### Aluminum / Steel



### Polyethylene Panels (1/2")



### Translucent resin panel (1/2")



Made at our factory in Lévis, Québec, Canada • Meets CAN/CSA-Z614 and ASTM ASTM F1487